

# Material Safety Data Sheet



Methylfuel™M1™

## 1. Product and company identification

**Product name** : Methylfuel™M1™  
**Material uses** : Fuel.  
**Supplier/Manufacturer** : VP Racing Fuels  
 7124 Richter Rd  
 Elmendorf, TX 78112  
**Validation date** : 09/30/2008  
**Responsible name** : Atrion Regulatory Services, Inc.  
**In case of emergency** : CHEMTREC, U.S. : +1-800-424-9300 International: +1-703-527-3887

## 2. Hazards identification

**Physical state** : Liquid. [Clear.]  
**Odor** : Alcohol-like.  
**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).  
**Emergency overview** : WARNING!  
 FLAMMABLE LIQUID AND VAPOR. HARMFUL IF INHALED OR SWALLOWED. CAUSES EYE IRRITATION. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE.  
 Flammable liquid. Harmful by inhalation and if swallowed. Irritating to eyes. Keep away from heat, sparks and flame. Avoid exposure - obtain special instructions before use. Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Contains material that can cause target organ damage. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.  
**Routes of entry** : Dermal contact. Inhalation. Ingestion.  
**Potential acute health effects**  
**Inhalation** : Harmful by inhalation.  
**Ingestion** : Harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause damage.  
**Skin** : May cause skin irritation.  
**Eyes** : Irritating to eyes.  
**Potential chronic health effects**  
**Chronic effects** : Contains material that can cause target organ damage.  
**Carcinogenicity** : No known significant effects or critical hazards.  
**Mutagenicity** : No known significant effects or critical hazards.  
**Teratogenicity** : No known significant effects or critical hazards.  
**Developmental effects** : No known significant effects or critical hazards.  
**Fertility effects** : No known significant effects or critical hazards.  
**Target organs** : Contains material which causes damage to the following organs: gastrointestinal tract, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.  
**Over-exposure signs/symptoms**  
**Inhalation** : No specific data.  
**Ingestion** : No specific data.  
**Skin** : No specific data.



## 2. Hazards identification

- Eyes** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Medical conditions aggravated by over-exposure** : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.
- See toxicological information (section 11)

## 3. Composition/information on ingredients

### United States

Name	CAS number	%
Methanol	67-56-1	>99.85%

### Canada

Name	CAS number	%
Methanol	67-56-1	>99.85%

### Mexico

Name	UN number	IDLH	Classification				CAS number	%
			H	F	R	Special		
Methanol	UN1230	6000 ppm	2	3	0	67-56-1	>99.85%	

## 4. First aid measures

- Eye contact** : Check for and remove any contact lenses. In case of contact with eyes, rinse immediately with plenty of water. Get medical attention.
- Skin contact** : In case of contact, immediately flush skin with plenty of water for at least 20 minutes. Get medical attention.
- Inhalation** : If inhaled, remove to fresh air. If not breathing, give artificial respiration. Get medical attention.
- Ingestion** : Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

## 5. Fire-fighting measures

- Flammability of the product** : Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.
- Extinguishing media**
- Suitable** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Not suitable** : Do not use water jet.

## 5 . Fire-fighting measures

- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Methods for cleaning up**
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

## 7 . Handling and storage

- Handling** : Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

## 7 . Handling and storage

**Storage** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## 8 . Exposure controls/personal protection

### United States

**Product name**

Methanol

**Exposure limits****ACGIH TLV (United States, 1/2007). Skin**STEL: 328 mg/m<sup>3</sup> 15 minute(s).

STEL: 250 ppm 15 minute(s).

TWA: 262 mg/m<sup>3</sup> 8 hour(s).

TWA: 200 ppm 8 hour(s).

**NIOSH REL (United States, 12/2001). Skin**STEL: 325 mg/m<sup>3</sup> 15 minute(s).

STEL: 250 ppm 15 minute(s).

TWA: 260 mg/m<sup>3</sup> 10 hour(s).

TWA: 200 ppm 10 hour(s).

**OSHA PEL (United States, 11/2006).**TWA: 260 mg/m<sup>3</sup> 8 hour(s).

TWA: 200 ppm 8 hour(s).

### Canada

**Product name**

Methanol

**Exposure limits****CA Alberta Provincial (Canada, 10/2006). Skin**8 hrs OEL: 262 mg/m<sup>3</sup> 8 hour(s).

8 hrs OEL: 200 ppm 8 hour(s).

15 min OEL: 250 ppm 15 minute(s).

15 min OEL: 328 mg/m<sup>3</sup> 15 minute(s).**CA British Columbia Provincial (Canada, 7/2007). Skin**

TWA: 200 ppm 8 hour(s).

STEL: 250 ppm 15 minute(s).

**CA Ontario Provincial (Canada, 3/2007). Skin**

TWAEV: 200 ppm 8 hour(s).

TWAEV: 260 mg/m<sup>3</sup> 8 hour(s).

STEV: 250 ppm 15 minute(s).

STEV: 325 mg/m<sup>3</sup> 15 minute(s).**CA Quebec Provincial (Canada, 12/2006). Skin**

TWAEV: 200 ppm 8 hour(s).

TWAEV: 262 mg/m<sup>3</sup> 8 hour(s).

STEV: 250 ppm 15 minute(s).

STEV: 328 mg/m<sup>3</sup> 15 minute(s).

### Mexico

**Product name**

Methanol

**Exposure limits****NOM-010-STPS (Mexico, 9/2000). Skin**LMPE-CT: 310 mg/m<sup>3</sup> 15 minute(s).




LMPE-CT: 250 ppm 15 minute(s).

LMPE-PPT: 260 mg/m<sup>3</sup> 8 hour(s).

LMPE-PPT: 200 ppm 8 hour(s).

Consult local authorities for acceptable exposure limits.

## 8 . Exposure controls/personal protection

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.
- Engineering measures** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Personal protection**
- Eyes** : Safety glasses.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory** : A respirator is not needed under normal and intended conditions of product use.
- Hands** : Disposable vinyl gloves.
- Personal protective equipment (Pictograms)** :
- 


- HMIS Code/Personal protective equipment** : B
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## 9 . Physical and chemical properties

- Physical state** : Liquid. [Clear.]
- Flash point** : Open cup: 15.85°C (60.5°F) [Cleveland.]
- Odor** : Alcohol-like.
- Relative density** : 0.792 [Water]
- Specific gravity** : 0.7915 g/cm<sup>3</sup> [20°C (68°F)]
- Vapor pressure** : 12.9 kPa (97 mm Hg)
- Evaporation rate** : 2.1 (Butyl acetate. = 1)

## 10 . Stability and reactivity

- Stability** : The product is stable.
- Hazardous polymerization** : Under normal conditions of storage and use, hazardous polymerization will not occur.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
- Materials to avoid** : Reactive or incompatible with the following materials: oxidizing materials.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.



## 10 . Stability and reactivity

**Conditions of reactivity** : Highly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge.  
Flammable in the presence of the following materials or conditions: heat.

## 11 . Toxicological information

### Acute toxicity

Product/ingredient name	Species	Dose	Result	Exposure
Methanol	Rabbit	15800 mg/kg	LD50 Dermal	-
	Rat	5600 mg/kg	LD50 Oral	-

**Inhalation** : Harmful by inhalation.

**Ingestion** : Harmful if swallowed. Aspiration hazard if swallowed. Can enter lungs and cause damage.

**Skin** : May cause skin irritation.

**Eyes** : Irritating to eyes.

### Carcinogenicity

#### Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
Methanol	-	-	-	None.	-	-

## 12 . Ecological information

**Environmental effects** : No known significant effects or critical hazards.

### Aquatic ecotoxicity

Product/ingredient name	Test	Species	Exposure	Result
Methanol	-	Daphnia	48 hours	Acute LC50 3289 to 4395 mg/L
	-	Fish	96 hours	Acute LC50 19 to 20 ml/L
	-	Crustaceans	48 hours	Acute LC50 2500000 ug/L

**Other adverse effects** : No known significant effects or critical hazards.

## 13 . Disposal considerations

**Waste disposal** : The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## 14 . Transport information

AERG : 131

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
<b>DOT Classification</b> (Domestic and non-bulk packaging.)	UN1230	METHANOL	3	II		<b>Limited quantity</b> Yes.  <b>Packing Instructions:</b> <b>Passenger aircraft</b> Quantity limitation: 1 L  <b>Cargo aircraft</b> Quantity limitation: 60 L  <b>Special provisions</b> IB2, T7, TP2  <b>Remarks</b> <b>Reportable quantity :</b> ≥ 5000 lbs
<b>DOT Classification</b> (Bulk)	UN1230	METHANOL	3	II		<b>Limited quantity</b> Yes.  <b>Packing Instructions:</b> <b>Passenger aircraft</b> Quantity limitation: 1 L  <b>Cargo aircraft</b> Quantity limitation: 60 L  <b>Special provisions</b> IB2, T7, TP2  <b>Remarks</b> <b>Reportable quantity :</b> ≥ 5000 lbs
<b>TDG Classification</b>	UN1230	METHANOL	3	II		<b>Special provisions</b> 43
<b>Mexico Classification</b>	UN1230	METHANOL	3	II		-
<b>IMDG Class</b>	UN1230	METHANOL	3 (6.1)	II	 	-



## 14 . Transport information

<b>IATA-DGR Class</b>	UN1230	METHANOL	3 (6.1)	II	 	<b>Passenger and Cargo Aircraft</b> Quantity limitation: 1 L <b>Cargo Aircraft Only</b> Quantity limitation: 60 L <b>Limited Quantities - Passenger Aircraft</b> Quantity limitation: 1 L
-----------------------	--------	----------	---------	----	------	---

PG\* : Packing group

## 15 . Regulatory information

### United States

**HCS Classification** : Flammable liquid  
Toxic material  
Irritating material  
Target organ effects

**U.S. Federal regulations** : **United States inventory (TSCA 8b)**: All components are listed or exempted.  
**SARA 302/304/311/312 extremely hazardous substances**: No products were found.  
**SARA 302/304 emergency planning and notification**: No products were found.  
**SARA 302/304/311/312 hazardous chemicals**: Methanol  
**SARA 311/312 MSDS distribution - chemical inventory - hazard identification**  
Methanol: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard  
**Clean Water Act (CWA) 307**: No products were found.  
**Clean Water Act (CWA) 311**: No products were found.  
**Clean Air Act (CAA) 112 accidental release prevention** No products were found.  
**Clean Air Act (CAA) 112 regulated flammable substances** No products were found.  
**Clean Air Act (CAA) 112 regulated toxic substances** No products were found.

### SARA 313

	<b>Product name</b>	<b>CAS number</b>	<b>Concentration</b>
<b>Form R - Reporting requirements</b>	: Methanol	67-56-1	60 - 100
<b>Supplier notification</b>	: Methanol	67-56-1	60 - 100

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

**State regulations** : **Connecticut Carcinogen Reporting**: None of the components are listed.  
**Connecticut Hazardous Material Survey**: None of the components are listed.  
**Florida substances**: None of the components are listed.  
**Illinois Chemical Safety Act** None of the components are listed.  
**Illinois Toxic Substances Disclosure to Employee Act** None of the components are listed.  
**Louisiana Reporting**: None of the components are listed.  
**Louisiana Spill**: None of the components are listed.  
**Massachusetts Spill**: None of the components are listed.  
**Massachusetts Substances**: The following components are listed: Methanol  
**Michigan Critical Material**: None of the components are listed.  
**Minnesota Hazardous Substances**: None of the components are listed.  
**New Jersey Hazardous Substances**: The following components are listed: Methanol  
**New Jersey Spill**: None of the components are listed.  
**New Jersey Toxic Catastrophe Prevention Act**: None of the components are listed.  
**New York Acutely Hazardous Substances**: The following components are listed:  
Methanol  
**New York Toxic Chemical Release Reporting**: None of the components are listed.  
**Pennsylvania RTK Hazardous Substances**: The following components are listed:

# 15 . Regulatory information

Methanol

**Rhode Island Hazardous Substances:** None of the components are listed.

**California Prop. 65**

**WARNING:** This product contains a chemical or chemicals known to the state of California to cause birth defects ( or other reproductive harm). Avoid breathing exhaust fumes and vapors. Do not use products in an indoor facility or in any facility without adequate ventilation.

**Canada**

**WHMIS (Canada)**

- : Class B-2: Flammable liquid
- Class D-1B: Material causing immediate and serious toxic effects (Toxic).
- Class D-2A: Material causing other toxic effects (Very toxic).
- Class D-2B: Material causing other toxic effects (Toxic).



**Canadian lists**

- : **CEPA Toxic substances:** None of the components are listed.
- Canadian ARET:** None of the components are listed.
- Canadian NPRI:** The following components are listed: Methanol
- Alberta Designated Substances:** None of the components are listed.
- Ontario Designated Substances:** None of the components are listed.
- Quebec Designated Substances:** None of the components are listed.

**Canada inventory**


- : **Canada inventory:** All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

**Mexico**

**Classification**

:



**International regulations**

**International lists**

- : This product, (and its ingredients) is (are) listed on national inventories, or is (are) exempted from being listed, in Australia (AICS), in Europe (EINECS/ELINCS), in Korea (TCCL), in Japan (METI), in the Philippines (RA6969).

## 16 . Other information

**Label requirements** : FLAMMABLE LIQUID AND VAPOR. HARMFUL IF INHALED OR SWALLOWED. CAUSES EYE IRRITATION. CONTAINS MATERIAL THAT CAN CAUSE TARGET ORGAN DAMAGE.

**Hazardous Material Information System (U.S.A.)** :

Health	*	2
Fire hazard		4
Physical Hazard		0
Personal protection		B


**HAZARD RATINGS**

- 4- Extreme
- 3- Serious
- 2- Moderate
- 1- Slight
- 0- Minimal

See section 8 for more detailed information on personal protection.

The customer is responsible for determining the PPE code for this material.

**National Fire Protection Association (U.S.A.)** :



**References** : ANSI Z400.5, MSDS Standard, 2004. - Manufacturer's Material Safety Data Sheet. - 29CFR Part1910.1200 OSHA MSDS Requirements. - 49CFR Table List of Hazardous Materials, UN#, Proper Shipping Names, PG. - Canada Gazette Part II, Vol. 122, No. 2. Registration SOR/88-64, 31 December 1987. Hazardous Products Act "Ingredient Disclosure List" - Canadian Transport of Dangerous Goods, Regulations and Schedules, Clear Language version 2005. - Official Mexican Standards NOM-018-STPS-2000 and NOM-004-SCT2-1994.

**Date of issue** : 09/30/2008  
**Date of previous issue** : 07/27/2007  
**Version** : 2

**Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.