



## DEXRON®-VI ATF

Kendall DEXRON®-VI ATF is a next-generation, full-synthetic transmission fluid approved for use in passenger car and light truck automatic transmissions that require a GM DEXRON®-VI or earlier generation DEXRON® fluid. It provides significantly improved oxidation stability, shear stability, friction durability and foam resistance compared with earlier generation DEXRON® fluids. It is specifically engineered to help ensure long service life, provide better performance under extreme operating conditions, and provide consistent shift performance for the life of the fluid. It is particularly recommended for use in new GM 6-speed automatic transmissions, and is fully backwards compatible for use in older GM automatic transmissions.

### **Applications**

DEXRON®-VI ATF is recommended for service fill in all automatic transmissions that require a GM DEXRON®-VI or earlier-generation DEXRON® fluid. It also may be used in hydraulic systems on industrial and mobile equipment operating over a wide temperature range.

DEXRON®-VI ATF meets or exceeds the requirements of:

- GM DEXRON®-VI
- Denison Hydraulics HF-0
- Vickers (Eaton) M-2950-S and I-286-S

### **Features/Benefits**

- Meets stricter performance requirements for new GM 6-speed automatic transmissions
- Outstanding friction durability for consistent shift performance for the life of the fluid
- Excellent oxidation resistance and thermal stability for long fluid life
- Protects against sludge and varnish formation
- Protects against wear
- Protects against rust and corrosion
- High shear stability
- Excellent low-temperature properties
- Good seal compatibility
- Good foam resistance
- Backwards compatible for use in older GM automatic transmissions

**GM DEXRON®-VI  
Automatic  
Transmission Fluid**

**Customer Service  
Number:  
1-800-368-7128**

**Technical Hot Line:  
1-800-368-1267**

**E-mail address:  
[kendallmotoroil@  
conocophillips.com](mailto:kendallmotoroil@conocophillips.com)**

**[www.kendallmotoroil.com](http://www.kendallmotoroil.com)**

**600 N. Dairy Ashford • 2W9000 • Houston, TX 77079**

**DEXRON®-VI ATF****Typical Properties**

Density, g/cm <sup>3</sup> @ 15.6°C (60°F)	0.844
Density, lbs/gal @ 15.6°C (60°F)	7.03
Color, Visual	Red
Flash Point (COC), °C (°F)	229 (444)
Pour Point, °C (°F)	-51 (-60)
Viscosity,	
cP @ -40°C (Brookfield)	11,500
cSt @ 40°C	29.8
cSt @ 100°C	6.0
SUS @ 100°F	152
SUS @ 210°F	46.3
Viscosity Index	151
Zinc, wt %	<0.002

**Health and Safety Information**

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Due to continual product research and development, the information contained herein is subject to change without notification.

Copyright © 2007 ConocoPhillips Company. The ConocoPhillips logo, Kendall and the Kendall logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.