



L-427 Super Blu®-Grease

Kendall L-427 Super Blu-Grease is a high-quality, multipurpose, extreme-pressure (EP) lithium complex grease developed to satisfy the severe lubrication requirements of heavily-loaded plain and rolling-element bearings operating at moderate to high temperatures. It is NLGI GC-LB certified for use as a multipurpose automotive wheel bearing and chassis lubricant.

L-427 Super Blu-Grease is manufactured with high-quality paraffinic base oils thickened with a lithium complex soap. It contains an extreme-pressure additive, a tackifier, and rust and oxidation inhibitors to provide excellent wear protection, excellent thermal stability at high temperatures, and excellent resistance to corrosion and water washout. It forms an effective seal to help minimize bearing contamination and provides a high level of adhesion to the bearing surface for improved retention, reduced leakage and enhanced resistance to water washout.

Applications

- Wheel bearings of passenger cars, trucks, high-performance vehicles, sport utility vehicles and motorcycles equipped with disc brakes
- Ball joints, universal joints, other chassis parts and water pumps on passenger cars, trucks and other mobile equipment
- Plain and rolling-element bearings operating under adverse conditions involving moisture and/or high temperatures
- Industrial and mobile equipment that require a high-temperature, water-resistant, extreme-pressure grease

L-427 Super Blu-Grease meets or exceeds the requirements of:

- Mack Specification MG-C for Chassis Lube
- NLGI GC-LB

Features/Benefits

- Excellent performance over a wide temperature range
- Excellent wear protection
- High load-carrying capacity
- Protects against rust and corrosion
- Excellent resistance to water washout
- NLGI GC-LB certified

**Multipurpose,
Extreme-Pressure
Lithium Complex
Grease; NLGI GC-LB
Certified**

**Customer Service
Number:
1-800-368-7128**

**Technical Hot Line:
1-800-368-1267**

**E-mail address:
*kendallmotoroil@
conocophillips.com***

www.kendallmotoroil.com

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



L-427 Super Blu®-Grease

Typical Properties

NLGI Grade	2
Thickener	Lithium Complex
Color	Blue
Dropping Point, °C (°F)	260 (500)
Density, lbs/gal	7.37
Penetration, Worked (60 strokes), ASTM D217	275
Texture	Smooth/Tacky
Four-Ball EP, ASTM D2596, Weld Load, kgf	250
Four-Ball Wear, ASTM D2266, Scar Diameter, mm	0.45
Oxidation Stability, ASTM D942, 100 hours, Pressure Drop, psi (kPa)	5 (35)
Rust Prevention, ASTM D1743	Pass
Timken OK Load, ASTM D2509, lb	45
Water Washout Resistance, ASTM D1264, Wt Loss @ 175°F, %	5
Base Oil Properties,	
Viscosity (with polymer),	
cSt @ 40°C	155
cSt @ 100°C	19.0
SUS @ 100°F	801
SUS @ 210°F	96.5
Viscosity Index	139
Usable Temperature Range,	
°C	-23 to 204
°F	-10 to 400

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Due to continual product research and development, the information contained herein is subject to change without notification.

Copyright © 2007 ConocoPhillips Company. The ConocoPhillips logo, Kendall and the Kendall logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.